



- 1.Engine: Japanese Robin 6.0HP or Honda 5.5HP four-stroke air-cooled gasoline engine.
- 2.Driving system: Imported oil pressurized continuously variable speed transmission with automatic brake device. The left wheels and right back wheels are equipped with a differential speed gearing to ensure it to drive freely around the curve and change directions timely. The foot-controlled brake device makes the driving more secure.
- 3.Driving speed: Forward: 0-4km/h; back off: 0-3km/h.
- 4.Maximum climbing capacity: 15°.
- 5.Chassis:A firm welded frame; its surface has been chrome-plated or sprayed with corrosion resistant coating; equipped with imported high-speed bearing which ensures the whole machine' running lighter and more convenient.
- 6.Rubber wheel: The left and the right wheels are gas-filled vacuum wheels whose diameter is 440mm.
- 7.Lighting function: Equipped with highlight light that makes the night construction more convenient.
- 8.Chair: The oblique angle and position of the chair can be freely adjusted according to the operator's needs.
- 9.Connecting device: The universal ball-type joint makes the connection between the roll booster and the equipment more convenient.
- 10.Size & Weight: 1400 mm (L) x720mm (W) x1080mm (H) · 140kg

- ◆1.引擎：日本罗宾6.0HP或本田5.5HP四冲程空冷式汽油发动机。
- ◆2.驱动系统：原装进口的带自动刹车装置且前进、后退及停止可灵便操作的油压式无级变速系统（HTS）；左右后轮为差速式传动装置，弯道行驶及转向时更灵活。带足控刹车装置，运行时更安全。
- ◆3.驱动速度：前进0-4km/h；后退0-3km/h。
- ◆4.最大爬坡能力：15°。
- ◆5.底盘：坚固焊接框架，表面经镀铬或抗腐蚀喷涂处理，配置高速型进口轴承，保证整机更轻盈、更灵便。
- ◆6.胶轮：左右轮均为充气式耐压真空轮，轮直径为440mm。
- ◆7.照明功能：随机所配的高亮度照明灯，方便夜间标线作业。
- ◆8.座椅：靠背角度及座位前后位置可根据操作员需要任意调整。
- ◆9.悬挂装置：万向球头式悬挂连接装置确保助推器与主机连接更自然。
- ◆10.外形尺寸·整机重量：1400 m（长）x 720 mm（宽）x 1080 mm（高）· 140kg。

DY-RB-II Roll Booster



DY-RB-I 搭乘式乘坐器 Roll Booster

- 1.Chassis: A firm welded frame; its surface has been chrome-plated or sprayed with corrosion resistant coating; equipped with imported high-speed bearing which ensures the whole machine' running lighter and more convenient.
- 2.Rubber wheel: The left and right wheels are gas-filled vacuum wheels, whose diameter is 440mm.
- 3.Chair: The oblique angle and position of the chair can be freely adjusted according to the operator's needs.
- 4.Connecting device: The universal ball-type joint makes the connection between the roll booster and the equipment more convenient.
- 5.Size & Weight: 1000 mm (L) x650 mm (W) x1020 mm (H) · 38kg.

- ◆1.底盘：坚固焊接框架，表面经镀铬或抗腐蚀喷涂处理，配置高速型进口轴承，保证整机更轻盈、更灵便。
- ◆2.胶轮：左右轮均为充气式耐压真空轮，轮直径为440mm。
- ◆3.座椅：靠背角度及座位前后位置可根据操作员需要任意调整。
- ◆4.悬挂装置：万向球头式悬挂连接装置确保助推器与主机连接更自然。
- ◆5.外形尺寸·整机重量：1000 mm（长）x 650 mm（宽）x 1020 mm（高）· 38kg。